

## WATER PURIFICATION EQUIPMENT AND METHOD OF CLEANING MEMBRANE ELEMENT

**Publication number:** JP2001190937

**Publication date:** 2001-07-17

**Inventor:** INOUE ISAMU

**Applicant:** SUMITOMO HEAVY INDUSTRIES

**Classification:**

- International: **B08B3/10; B01D65/02; B01D65/04; B01D65/08;**  
**C02F1/44; C02F3/12; C02F1/44; B08B3/10;**  
**B01D65/00; C02F1/44; C02F3/12; C02F1/44; (IPC1-7):**  
**B01D65/08; B01D65/02; B01D65/04; B08B3/10;**  
**C02F1/44; C02F3/12**

- European:


**Application number:** JP20000000912 20000106

**Priority number(s):** JP20000000912 20000106

[Report a data error here](#)

### Abstract of JP2001190937

**PROBLEM TO BE SOLVED:** To provide a water purification equipment excellent performance to remove the solid content attached to the surface of a membrane element as well as capable of sufficiently preventing damages on the surface of the membrane element, and a method for cleaning the membrane element. **SOLUTION:** The water purification equipment 1 is provided with a treating tank 11 to which a water to be treated is supplied, a flat membrane 33 which is immersed in the water W to be treated to obtain a treated water by the membrane filtration of the water to be treated, a bubbling equipment 25 generating air bubbles 3 in the treating tank 11 and a floating solid 2 capable of floating on a gas-liquid interface in the treating tank 11. At the time of cleaning a flat membrane 33, the solid content attached to the surface of the membrane is efficiently cleaned by transferring the gas-liquid interface within a range between both up and down ends of the flat membrane 33 and vibrating the floating solid 2 to strongly rub with the flat membrane 33. The damages on the surface of the membrane are prevented because the floating solid 2 comes into contact with the surface of the membrane only at the time of washing.



Data supplied from the esp@cenet database - Worldwide